


FKOA/RM

Spjeldventil med gir EPDM

- ABS- spjeldventil
- Hus: Glassfylt PP, UV- beskyttet
- EPDM
- Spjeld i ABS
- PN 10
- Påmontert gir
- Montering av aktuator iht. ISO 5211
- Kontroller frigang av spjeld i krage før montering
- For større dimensjoner se PP



Artikkelnr	d	DN	PN	A	B2	B5	B6	G1	G2	Z
FKOA/RM-E-075	75	65	10	46	80.0	174.0	146.0	135	39	46
FKOA/RM-E-090	90	80	10	49	93.0	188.0	160.0	135	39	49
FKOA/RM-E-110	110	100	10	56	107.0	202.0	174.0	135	39	56
FKOA/RM-E-140	140	125	10	64	120.0	222.0	194.0	144	39	64
FKOA/RM-E-160	160	150	10	70	134.0	235.0	207.0	144	39	70
FKOA/RM-E-225	225	200	10	71	161.0	287.0	256.0	204	60	71
FKOA/RM-E-280	280	250	10	114	210.0	317.0	281.0	236	76	114
FKOA/RM-E-315	315	300	8	114	245.0	374.0	338.0	236	76	114
FKOA/RM-V-075	75	65	10	46	80.0	174.0	146.0	135	39	46
FKOA/RM-V-090	90	80	10	49	93.0	188.0	160.0	135	39	49
FKOA/RM-V-110	110	100	10	56	107.0	202.0	174.0	135	39	56
FKOA/RM-V-140	140	125	10	64	120.0	222.0	194.0	144	39	64
FKOA/RM-V-160	160	150	10	70	134.0	235.0	207.0	144	39	70
FKOA/RM-V-225	225	200	10	71	161.0	287.0	256.0	204	60	71
FKOA/RM-V-280	280	250	10	114	210.0	317.0	281.0	236	76	114
FKOA/RM-V-315	315	300	8	114	245.0	374.0	338.0	236	76	114