


FKOM/RM

Spjeldventil med gir EPDM

- PP- spjeldventil
- Hus: Glassfylt PP, UV -beskyttet
- EPDM
- Klaff PP
- PN 10
- Maks 90
- Gir.
- Montering av aktuator iht. ISO 5211, med ekstra tilbehør.
- Kontrollere fri gang av spjeld i krage før montering.




Artikkelnr	NRF	d	DN	G	PN	B2	B5	B6	G1	H	Tetning smateriale
FKOM/RM-E-075	5601536	75	65	48	10	80.0	174.0	146.0	135	165	EPDM
FKOM/RM-E-090	5601537	90	80	48	10	93.0	188.0	160.0	135	185	EPDM
FKOM/RM-E-110	5601538	110	100	48	10	107.0	202.0	174.0	135	211	EPDM
FKOM/RM-E-140	5601539	140	125	48	10	120.0	222.0	194.0	144	240	EPDM
FKOM/RM-E-160	5601541	160	150	48	10	134.0	235.0	207.0	144	268	EPDM
FKOM/RM-E-225	5601542	225	200	65	10	161.0	287.0	256.0	204	323	EPDM
FKOM/RM-E-280	5601543	280	250	88	10	210.0	317.0	281.0	236	405	EPDM
FKOM/RM-E-315	5601544	315	300	88	10	210.0	317.0	281.0	236	405	EPDM
FKOM/RM-E-355	5601346	355	350	88	7	280.0	438.0	390.0	361	530	EPDM
FKOM/RM-E-400	5601347	400	400	88	6	306.0	438.0	390.0	361	594	EPDM
FKOM/RM-V-075		75	65	48	10	80.0	174.0	146.0	135	165	FPM
FKOM/RM-V-090		90	80	48	10	93.0	188.0	160.0	135	185	FPM
FKOM/RM-V-110		110	100	48	10	107.0	202.0	174.0	135	211	FPM
FKOM/RM-V-140		140	125	48	10	120.0	222.0	194.0	144	240	FPM
FKOM/RM-V-160		160	150	48	10	134.0	235.0	207.0	144	268	FPM
FKOM/RM-V-225		225	200	65	10	161.0	287.0	256.0	204	323	FPM
FKOM/RM-V-280		280	250	88	10	210.0	317.0	281.0	236	405	FPM
FKOM/RM-V-315		315	300	88	10	210.0	317.0	281.0	236	405	FPM
FKOM/RM-V-355		355	350	88	7	280.0	438.0	390.0	361	530	FPM

Med forbehold om konstruksjonsendringer og tekniske endringer. Kan endres uten varsel.

gpa.no | info@gpa.no | +47 64 85 68 00

FKOM/RM

Spjeldventil med gir EPDM



Artikkelnr	NRF	d	DN	G	PN	B2	B5	B6	G1	H	Tetning smateri ale
FKOM/RM-V-400		400	400	88	6	306.0	438.0	390.0	361	594	FPM