


K40U/RM

Dreiespjeldsventil m/gir EPDM

- PVC-dreiespjeldsventil
- Hus i glassforsterket PP, UV-beskyttet
- Spjeldblad i PVC
- EPDM-liner
- PN 10
- Maks 60°C
- Påmontert gir
- Kontroller klaring for spjeld i krage før montering.



Artikkelnr	NRF	d	DN	A	C	D	F	H	h	N	Z
K40U/RM-E-075	5516045	75	65	120	133	65	232	308	100.0	52	46
K40U/RM-E-110	5516046	110	100	121	206	100	269	357.5	115.0	52	56
K40U/RM-E-140	5516047	140	125	121	234.5	125	303.5	392	130.0	52	64
K40U/RM-E-160	5516048	160	150	122	261	150	337.5	447.5	147.5	60	70
K40U/RM-E-225	5516049	225	200	122	314	200	399.5	509.5	175.0	60	71
K40U/RM-V-075		75	65	120	133	65	232	308	100.0	52	46
K40U/RM-V-090		90	80	120	176	80	239	315	100.0	52	49
K40U/RM-V-110		110	100	121	206	100	269	357.5	115.0	52	56
K40U/RM-V-140		140	125	121	234.5	125	303.5	392	130.0	52	64
K40U/RM-V-160		160	150	122	261	150	337.5	447.5	147.5	60	70
K40U/RM-V-225		225	200	122	314	200	399.5	509.5	175.0	60	71