

SIL

Silduk for filter

- PVC-silrør til filter RV
- Standard leveres det 500 Micron i filtret



Artikkelnr	d	ASTM mesh	Fri scrimoverflate cm ²	Hull/cm ²	Maskeavstand (mm)	Micron
SIL020-10	16-20	50.0	16.0	190.0	1.0	300.0
SIL020-15	16-20	35.0	16.0	100.0	1.5	500.0
SIL020-25	16-20	18.0	16.0	35.0	2.5	900.0
SIL025-10	25	50.0	24.0	190.0	1.0	300.0
SIL025-15	25	35.0	24.0	100.0	1.5	500.0
SIL025-25	25	18.0	24.0	35.0	2.5	900.0
SIL032-10	32	50.0	36.0	190.0	1.0	300.0
SIL032-15	32	35.0	36.0	100.0	1.5	500.0
SIL032-25	32	18.0	36.0	35.0	2.5	900.0
SIL040-10	40	50.0	53.0	190.0	1.0	300.0
SIL040-15	40	35.0	53.0	100.0	1.5	500.0
SIL040-25	40	18.0	53.0	35.0	2.5	900.0
SIL050-10	50	50.0	69.0	190.0	1.0	300.0
SIL050-15	50	35.0	69.0	100.0	1.5	500.0
SIL050-25	50	18.0	69.0	35.0	2.5	900.0
SIL063-10	63	50.0	101.0	190.0	1.0	300.0
SIL063-15	63	35.0	101.0	100.0	1.5	500.0
SIL063-25	63	18.0	101.0	35.0	2.5	900.0
SIL075-10	75	50.0	197.0	190.0	1.0	300.0
SIL075-15	75	35.0	197.0	100.0	1.5	500.0
SIL075-25	75	18.0	197.0	35.0	2.5	900.0
SIL090-10	90	50.0	247.0	190.0	1.0	300.0

Med forbehold om konstruksjonsendringer og tekniske endringer. Kan endres uten varsel.

gpa.no | info@gpa.no | +47 64 85 68 00

SIL

Silduk for filter



Artikkelnr	d	ASTM mesh	Fri scrimoverflat e cm ²	Hull/cm ²	Maskeavstan d (mm)	Micron
SIL090-15	90	35.0	247.0	100.0	1.5	500.0
SIL090-25	90	18.0	247.0	35.0	2.5	900.0
SIL110-10	110	50.0	396.0	190.0	1.0	300.0
SIL110-15	110	35.0	396.0	100.0	1.5	500.0
SIL110-25	110	18.0	396.0	35.0	2.5	900.0