


## TKDIC

### Innv. lim T-boret EPDM

- CPVC-kuleventil, 3-veis
- Innvendig lim
- T-boret kule
- Utstyrt med Dual block som holder mutteren i posisjon, samt tag for merking.
- Fast sete, en side av ventilen kan demonteres under fullt trykk.
- PN 16
- EPDM



| Artikkelnr  | d  | DN | B x B1  | C x C1 | E   | H   | H1  | L  | Vekt   | Z   |
|-------------|----|----|---------|--------|-----|-----|-----|----|--------|-----|
| TKDIC-E-016 | 16 | 10 | 54x29   | 67x40  | 55  | 118 | 80  | 14 | 310 g  | 90  |
| TKDIC-E-020 | 20 | 15 | 54x29   | 67x40  | 55  | 118 | 80  | 16 | 310 g  | 86  |
| TKDIC-E-025 | 25 | 20 | 65x34.5 | 85x49  | 66  | 145 | 100 | 19 | 550 g  | 107 |
| TKDIC-E-032 | 32 | 25 | 69.5x39 | 85x49  | 75  | 160 | 110 | 22 | 790 g  | 116 |
| TKDIC-E-040 | 40 | 32 | 82.5x46 | 108x64 | 87  | 189 | 131 | 26 | 1275 g | 137 |
| TKDIC-E-050 | 50 | 40 | 89x52   | 108x64 | 100 | 219 | 148 | 31 | 1660 g | 157 |
| TKDIC-E-063 | 63 | 50 | 108x62  | 134x76 | 122 | 267 | 179 | 38 | 2800 g | 191 |
| TKDIC-V-016 | 16 | 10 | 54x29   | 67x40  | 55  | 118 | 80  | 14 | 310 g  | 90  |
| TKDIC-V-020 | 20 | 15 | 54x29   | 67x40  | 55  | 118 | 80  | 16 | 310 g  | 86  |
| TKDIC-V-025 | 25 | 20 | 65x34.5 | 85x49  | 66  | 145 | 100 | 19 | 550 g  | 107 |
| TKDIC-V-032 | 32 | 25 | 69.5x39 | 85x49  | 75  | 160 | 110 | 22 | 790 g  | 116 |
| TKDIC-V-040 | 40 | 32 | 82.5x46 | 108x64 | 87  | 189 | 131 | 26 | 1275 g | 137 |
| TKDIC-V-050 | 50 | 40 | 89x52   | 108x64 | 100 | 219 | 148 | 31 | 1660 g | 157 |
| TKDIC-V-063 | 63 | 50 | 108x62  | 134x76 | 122 | 267 | 179 | 38 | 2800 g | 191 |