


## TR40U

### T-rør redusert

- PVC-T-rør 90° med redusert uttak
- Innvendig lim
- PN 16 d20-d160
- PN 10 d200-d315




Artikkelnr	NRF	d	d1	E	E1	L	L1	Z	Z1
TR40U-063-050	2439586	63	50	75	61.0	38	31	33	33.0
TR40U-075-040		75	40	89	51.0	44	26	39	39.0
TR40U-075-032		75	32	89	42.0	44	22	39	39.0
TR40U-075-050	1388585	75	50	89	61.0	44	31	39	39.0
TR40U-250-160		250	160	288	184.0	132	86	128	128.0
TR40U-090-040		90	40	106	51.0	51	26	47	47.0
TR40U-075-063		75	63	89	75.0	44	38	39	39.0
TR40U-025-020	2439572	25	20	34	24.0	19	14	14	14.0
TR40U-090-050		90	50	106	61.0	51	31	47	47.0
TR40U-032-020	2439573	32	20	42	28.0	22	16	17	17.0
TR40U-090-063		90	63	106	75.0	51	38	47	47.0
TR40U-040-020	2439575	40	20	51	28.0	26	16	21	21.0
TR40U-032-025	2439574	32	25	42	34.0	22	19	17	17.0
TR40U-110-050		110	50	129	61.0	61	31	57	57.0
TR40U-090-075		90	75	106	89.0	51	44	47	47.0
TR40U-040-025	2439576	40	25	51	34.0	26	19	21	21.0
TR40U-110-063		110	63	129	75.0	61	38	57	57.0
TR40U-050-020	2439578	50	20	61	28.0	31	16	26	26.0
TR40U-040-032	2439577	40	32	51	42.0	26	22	21	21.0
TR40U-110-090		110	90	129	106.0	61	51	57	57.0
TR40U-110-075		110	75	129	89.0	61	44	57	57.0
TR40U-050-025	2439579	50	25	61	34.0	31	19	26	26.0
TR40U-050-032	2439581	50	32	61	42.0	31	22	26	26.0

Med forbehold om konstruksjonsendringer og tekniske endringer. Kan endres uten varsel.

[gpa.no](http://gpa.no) | [info@gpa.no](mailto:info@gpa.no) | +47 64 85 68 00

## TR40U

### T-rør redusert



Artikkelnr	NRF	d	d1	E	E1	L	L1	Z	Z1
TR40U-050-040	2439582	50	40	61	51.0	31	26	26	26.0
TR40U-063-025	2439583	63	25	75	34.0	38	19	33	33.0
TR40U-063-032	2439584	63	32	75	42.0	38	22	33	33.0
TR40U-063-040	2439585	63	40	75	51.0	38	26	33	33.0
TR40U-160-140		160	140	184	163.0	86	76	82	82.0
TR40U-090-032-P		90	32	110	42.5	51	51	46	46
TR40U-200-110-V		200	110	-	-	107	61	106	131
TR40U-200-160-V		200	160	-	-	107	86	106	106
TR40U-225-110-V		225	110	-	-	120	61	119	143
TR40U-225-160-V		225	160	-	-	120	86	119	119
TR40U-280-160-V		280	160	-	-	146	86	120	180
TR40U-280-225-V		280	225	-	-	146	119	120	149
TR40U-315-160-V		315	160	-	-	164	86	120	197
TR40U-315-225-V		315	225	-	-	164	119	120	165