



UVM

Sadel

- PPs-sadel med muffe
- Ventilasjon
- Andre dimensjoner ved forespørsel
- Finnes også som 45° av type UVHM
- UVE=PE
- UVMP=PP





Artikkelnr	Rør D	Da Ø	L	L1	S
UVM 090-075	90.0	75.0	40	1.9	4.5
UVM 110-090	110.0	90.0	40	2.2	5.4
UVM 125-090	125.0	90.0	40	2.2	5.4
UVM 125-110	125.0	110.0	40	2.7	3.4
UVM 140-110	140.0	110.0	40	2.7	3.4
UVM 160-090	160.0	90.0	40	2.2	5.4
UVM 160-110	160.0	110.0	40	2.7	3.4
UVM 180-110	180.0	110.0	40	2.7	3.4
UVM 200-110	200.0	110.0	40	2.7	3.4
UVM 225-160	225.0	160.0	40	4	4
UVM 250-110	250.0	110.0	40	2.7	3.4
UVM 250-160	250.0	160.0	40	4	4
UVM 250-200	250.0	200.0	40	3	6.2
UVM 280-160	280.0	160.0	40	4	4
UVM 315-110	315.0	110.0	40	2.7	3.4
UVM 315-160	315.0	160.0	40	4	4
UVM 315-200	315.0	200.0	40	3	6.2
UVM 355-200	355.0	200.0	40	3	6.2
UVM 355-250	355.0	250.0	40	3.5	6.2
UVM 400-250	400.0	250.0	40	3.5	6.2
UVM 500-200	500.0	200.0	40	3	6.2
UVM 500-315	500.0	315.0	50	5	7.7
UVM 600-315	600.0	315.0	50	5	7.7

Med forbehold om konstruksjonsendringer og tekniske endringer. Kan endres uten varsel.

gpa.no | info@gpa.no | +47 64 85 68 00

UVM

Sadel



Artikkelnr	Rør D	Da Ø	L	L1	S
UVM 630-315	630.0	315.0	50	5	7.7
UVM 400-200	400.0	200.0	40	3	6.2