


## UVV

### Sadel med muffe

- PVC-sadel med muffe
- Ventilasjon
- Grå (hvit på forespørsel)
- Andre dimensjoner ved forespørsel
- Finnes også som 45° av type UVHV




| Artikkelnr  | Rør D | Da Ø  | L  | L1  | S   |
|-------------|-------|-------|----|-----|-----|
| UVV 090-075 | 90.0  | 75.0  | 40 | 2.5 | 3   |
| UVV 110-075 | 110.0 | 75.0  | 40 | 2.5 | 3   |
| UVV 110-090 | 110.0 | 90.0  | 40 | 2.5 | 3   |
| UVV 125-090 | 125.0 | 90.0  | 40 | 2.5 | 3   |
| UVV 140-110 | 140.0 | 110.0 | 40 | 2.5 | 3   |
| UVV 160-110 | 160.0 | 110.0 | 40 | 2.5 | 3   |
| UVV 180-110 | 180.0 | 110.0 | 40 | 2.5 | 3   |
| UVV 200-110 | 200.0 | 110.0 | 40 | 2.5 | 3   |
| UVV 200-160 | 200.0 | 160.0 | 40 | 2.5 | 3   |
| UVV 225-160 | 225.0 | 160.0 | 40 | 2.5 | 3   |
| UVV 250-110 | 250.0 | 110.0 | 40 | 2.5 | 3   |
| UVV 250-160 | 250.0 | 160.0 | 40 | 2.5 | 3   |
| UVV 250-200 | 250.0 | 200.0 | 40 | 2.5 | 3   |
| UVV 280-160 | 280.0 | 160.0 | 40 | 2.5 | 3   |
| UVV 315-110 | 315.0 | 110.0 | 40 | 2.5 | 3   |
| UVV 315-160 | 315.0 | 160.0 | 40 | 2.5 | 3   |
| UVV 315-200 | 315.0 | 200.0 | 40 | 2.5 | 3   |
| UVV 355-200 | 355.0 | 200.0 | 40 | 2.5 | 3   |
| UVV 355-250 | 355.0 | 250.0 | 40 | 2.5 | 3.5 |
| UVV 400-200 | 400.0 | 200.0 | 40 | 2.5 | 3   |
| UVV 500-200 | 500.0 | 200.0 | 40 | 2.5 | 3   |
| UVV 500-315 | 500.0 | 315.0 | 50 | 2.5 | 5   |
| UVV 600-315 | 600.0 | 315.0 | 50 | 2.5 | 5   |

Med forbehold om konstruksjonsendringer og tekniske endringer. Kan endres uten varsel.

[gpa.no](http://gpa.no) | [info@gpa.no](mailto:info@gpa.no) | +47 64 85 68 00

## UVV

### Sadel med muffe



| Artikkelnr  | Rør D | Da Ø  | L  | L1  | S   |
|-------------|-------|-------|----|-----|-----|
| UVV 800-250 | 800.0 | 250.0 | 40 | 2.5 | 3.5 |