


VKDIA/NC

Kuleventil innv. lim pneumatisk (NC) EPDM

- ABS-kuleventil, 2-veis, innv. lim
- Pneumatisk normalt stengt (NC)
- EPDM
- PN 10
- Tilkobling styrluft: G1/4" Namur
- Styrtrykk: 5,5-8 Bar
- Optisk indikering
- * Tilbehør og aktuator, se kapittel PVC



Artikkelnr	d	DN	B	Don	H	H1	H2	K	L
VKDIA/NC-E-020	20	15	141	PPW/S	143	58	29.0	68	103
VKDIA/NC-E-025	25	20	141	PPW/S	159	74	35.0	68	115
VKDIA/NC-E-032	32	25	149	PP00/S	184	74	39.0	80	128
VKDIA/NC-E-040	40	32	149	PP00/S	207	97	45.0	80	146
VKDIA/NC-E-050	50	40	222	PP10/S	232	104	52.0	97	164
VKDIA/NC-E-063	63	50	222	PP10/S	242	114	62.0	97	199
VKDIA/NC-E-075	75	65	292	PP20/S	280	119	87.0	125	235
VKDIA/NC-E-090	90	80	292	PP20/S	292	132	105.0	125	270
VKDIA/NC-E-110	110	100	292	PP20/S	310	150	129.0	125	308
VKDIA/NC-V-020	20	15	141	PPW/S	143	58	29.0	68	103
VKDIA/NC-V-025	25	20	141	PPW/S	159	74	35.0	68	115
VKDIA/NC-V-032	32	25	149	PP00/S	184	74	39.0	80	128
VKDIA/NC-V-040	40	32	149	PP00/S	207	97	45.0	80	146
VKDIA/NC-V-050	50	40	222	PP10/S	232	104	52.0	97	164
VKDIA/NC-V-063	63	50	222	PP10/S	242	114	62.0	97	199
VKDIA/NC-V-075	75	65	292	PP20/S	280	119	87.0	125	235
VKDIA/NC-V-090	90	80	292	PP20/S	292	132	105.0	125	270
VKDIA/NC-V-110	110	100	292	PP20/S	310	150	129.0	125	308