


VKDIC

Kuleventil Industri EPDM

- CPVC-kuleventil
- Innvendig lim
- Utstyrt med Dual block som holder mutteren i posisjon, samt tag for merking.
- Fast sete, en side av ventilen kan demonteres under fullt trykk.
- PN 16
- EPDM



Artikkelnr	d	DN	B	C x C1	E	H	H1	L	Vekt	Z
VKDIC-E-016	16	10	54	67x40	54	103	65	14	234 g	75
VKDIC-E-020	20	15	54	67x40	54	103	65	16	223 g	71
VKDIC-E-025	25	20	65	85x49	65	115	70	19	358 g	77
VKDIC-E-032	32	25	69.5	85x49	73	128	78	22	476 g	84
VKDIC-E-040	40	32	82.5	108x64	86	146	88	26	753 g	94
VKDIC-E-050	50	40	89	108x64	98	164	93	31	1007 g	102
VKDIC-E-063	63	50	108	134x76	122	199	111	38	1717 g	123
VKDIC-E-075	75	65	164	225x175	164	235	133	44	4750 g	147
VKDIC-E-090	90	80	177	327x272	203	270	149	51	7838 g	168
VKDIC-E-110	110	100	195	385x330	238	308	167	61	12137 g	186
VKDIC-V-016	16	10	54	67x40	54	103	65	14	234 g	75
VKDIC-V-020	20	15	54	67x40	54	103	65	16	223 g	71
VKDIC-V-025	25	20	65	85x49	65	115	70	19	358 g	77
VKDIC-V-032	32	25	69.5	85x49	73	128	78	22	476 g	84
VKDIC-V-040	40	32	82.5	108x64	86	146	88	26	753 g	94
VKDIC-V-050	50	40	89	108x64	98	164	93	31	1007 g	102
VKDIC-V-063	63	50	108	134x76	122	199	111	38	1717 g	123
VKDIC-V-075	75	65	164	225x175	164	235	133	44	4750 g	147
VKDIC-V-090	90	80	177	327x272	203	270	146	51	7838 g	168
VKDIC-V-110	110	100	195	385x330	238	308	167	61	12137 g	186

Med forbehold om konstruksjonsendringer og tekniske endringer. Kan endres uten varsel.

gpa.no | info@gpa.no | +47 64 85 68 00