


VKDIV/NC

Kuleventil pneumatisk (NC) EPDM

- PVC-kuleventil
- Pneumatisk normalt stengt (NC)
- Utstyrt med Dual block som holder mutteren i posisjon, samt tag for merking. Fast sete, en side av ventilen kan demonteres under fullt trykk.
- PN 16
- EPDM
- Maks 60°C
- Tilkobling styrluft: G1/4" Namur
- Styretrykk: 5,5-8 Bar
- Optisk indikering
- Tilbehør: se kommende sider




Artikkelnr	d	DN	B	Don	H	H1	H2	K	L
VKDIV/NC-E-016									
VKDIV/NC-E-020	20	15	141	PPW/S	143	58	29.0	68	103
VKDIV/NC-E-025	25	20	141	PPW/S	159	74	35.0	68	115
VKDIV/NC-E-032	32	25	149	PP00/S	184	74	39.0	80	128
VKDIV/NC-E-040	40	32	149	PP00/S	207	97	46.0	80	146
VKDIV/NC-E-050	50	40	222	PP10/S	232	104	52.0	97	164
VKDIV/NC-E-063	63	50	222	PP10/S	242	114	62.0	97	199
VKDIV/NC-E-075	75	65	292	PP20/S	280	119	87.0	125	235
VKDIV/NC-E-090	90	80	292	PP20/S	292	132	105.0	125	270
VKDIV/NC-E-110	110	100	292	PP20/S	310	150	129.0	125	308
VKDIV/NC-V-016									
VKDIV/NC-V-020	20	15	141	PPW/S	143	58	29.0	68	103
VKDIV/NC-V-025	25	20	141	PPW/S	159	74	35.0	68	115
VKDIV/NC-V-032	32	25	149	PP00/S	184	74	39.0	80	128
VKDIV/NC-V-040	40	32	149	PP00/S	207	97	46.0	80	146
VKDIV/NC-V-050	50	40	222	PP10/S	232	104	52.0	97	164
VKDIV/NC-V-063	63	50	222	PP10/S	242	114	62.0	97	199
VKDIV/NC-V-075	75	65	292	PP20/S	280	119	87.0	125	235

Med forbehold om konstruksjonsendringer og tekniske endringer. Kan endres uten varsel.

gpa.no | info@gpa.no | +47 64 85 68 00

VKDIV/NC

Kuleventil pneumatisk (NC)
EPDM



Artikkelnr	d	DN	B	Don	H	H1	H2	K	L
VKDIV/NC-V-090	90	80	292	PP20/5	292	132	105.0	125	270
VKDIV/NC-V-110	110	100	292	PP20/5	310	150	129.0	125	308
VKDIV/NO-E-025									
VKDIV/NO-E-032									
VKDIV/PGB-NC-E-025									
VKDIV/PGB-NC-E-032									
VKDIV/PGB-NC-E-063									